

## Tiger Canyon i3 – Tall Chassis

### A leap forward in Business Performance

Boundary-breaking performance is available with the latest 11th Gen Intel® Core™ i3 processors with UHD graphics and support for high-speed 3200 MHz DDR4 memory. Whether you're creating a digital kiosk, deploying intelligent vending, or refreshing enterprise PCs, Tiger Canyon can get the job done easily. Tiger Canyon SKUs also feature technology hardware-enhanced security features, and platform stability to help businesses cut IT costs and boost uptime.

### More Performance. More Connections

Every Intel NUC 11 Pro system can support one 8K or four 4K displays for digital signage, video conferencing, and other deployments. Businesses can get more work done anytime,

anyplace, with the latest wired and wireless options, like Intel® Wi-Fi 6 AX201, the fastest generation of Wi-Fi, and two ultra-fast Thunderbolt™ ports.

### Build embedded solutions

Tiger Canyon, built on Intel 11th Gen architecture, provides greater system performance over previous generations with advanced hyperthreading technologies driving faster speeds and enhanced graphics. Qualified for 24x7 operation and backed by a three-year warranty, Intel NUC 11 Pro boards are small, powerful systems designed to meet today's needs—and keep businesses running for years. The built-in hardware-enhanced security keeps client data and credentials secure for remote installations such as digital kiosks and intelligent vending.

### Highlighted features

- 11<sup>th</sup> Gen Intel® Core™ i3-1115G4
- Intel® UHD Graphics
- 2x DDR4-3200 SO-DIMM Sockets
- M.2 Socket Supports PCIe Gen 4 SSDs
- Secondary M.2 Slot Supports SATA 2.5" SSD (7mm)
- 2x HDMI 2.0b Supporting 4K @ 60Hz
- Intel® 2.5 Gigabit LAN
- Intel® Wi-Fi 6 + Bluetooth 5.1
- 1x Thunderbolt 4 Port
- 1x Thunderbolt 3 Port
- 3x USB Gen 2 Ports
- 1x USB 2.0 Port
- Digital Audio 7.1 Surround Sound
- Internal Dual-Band Antennas
- Front Panel Power Button
- 19V<sub>DC</sub> Power Supply
- Kensington Lock Support
- VESA Mount Kit

### Customization

- Chassis Expansions incl. Dual LAN/USB 2.0 Expansion
- Supports DDR4 RAM 4GB to 64GB
- Supports M.2 SSD 128GB to 8TB
- Secondary M.2 Supports 2.5" SSD 128GB to 8TB
- 2s USB 2.0 Internal Headers
- 1x RS-232 Serial Internal Header
- Customizable Lid Options



### Simply NUC Services

You can order this NUC in your various configurations, as well as your corporate OS Image loaded and ready to deploy.

## Technical Specification

### Processor

- 11<sup>th</sup> Gen Intel® Core™ i3-1115G4 processor (1.7GHz @ 28W, up to 3GHz Turbo, 2 Cores, 4 Threads, 6MB Cache)

### Graphics

- Intel® UHD Graphics
- 2x HDMI 2.0b Ports with HDCP 2.2
- Built-in CEC for Both Ports
- Support for a 3<sup>rd</sup> and 4<sup>th</sup> Monitor via Thunderbolt 4 with DisplayPort

### System Memory

- 2x DDR4 SO-DIMM Sockets, up to 64GB, 3200MHz, 1.2V

### Storage Capabilities

- M.2 22x80 Socket Supports SSDs and PCIe Gen 4
- M.2 Socket for Connection to 2.5" SATA SSD

### Peripheral Connectivity

- Intel® 2.5 Gigabit LAN
- 3x Super-Speed USB 3.2 Gen 2 Ports (2x Front and 1x Rear)
- 1x Rear USB 2.0 Port
- 2x Rear USB 3.2 Gen 2 Ports on Type-C Connector (1x Thunderbolt 4; 1x Thunderbolt 3)
- Intel® Wi-Fi 6 AX201 is Removable or Disabled for Security
- Intel® Bluetooth 5.1
- Optional Chassis Expansion Intel® 2.5 Gigabit LAN with Two USB 2.0

### System Bios

- 64Mb Flash EEPROM with Intel® Platform Innovation Framework for EFI Plug and Play
- Intel® Visual BIOS
- Intel® Express Bios Update Support

### Audio

- Up to 7.1 Multichannel (or Dual 8-channel) Digital Audio via HDMI

### Mechanical Chassis Information

- 4.61" x 4.41" x 2.13" (117mm x 112mm x 54mm)

### Hardware Management Features

- Voltage and Temperature Sensing
- ACPI-compliant Power Management Control
- Fan Sensor Input used to Monitor and Control Fan Activity

### Baseboard Power Requirements

- 12V<sub>DC</sub> to 20V<sub>DC</sub> Input Voltage Range
- 19V AC-DC Power Adapter with Detachable Power Cord Supplied

### Expansion Capabilities

- 1x M.2 for Panel Expansion and Functional Lid Support—incl. Dual LAN/USB 2.0 Expansion Panel
- 2x USB 2.0 Ports on Two 1x4 Internal Headers
- 2x Consumer Electronics Control Headers

### Front Panel Header

- Reset, HDD LED, Power LEDs, Power On/Off
- Vcc5/1A, 5Vsby/2A, 3.3Vsby/1A

## Certifications and Regulation

### Safety Regulations and Standards

- IEC 60950-1
- UL 60950-1
- EN 60950-1
- CAN/CSA-C22.2 No. 60950-1

### EMC/RF Regulations and Standards

- FCC CFR Title 47, Chapter I, Part 15, Subparts B, C, E
- EN 55052
- EN 55024
- CISPR 52
- ICES-005
- ETSI EN 500 528
- ETSI EN 501 489-1
- ETSI EN 501 489-17
- ETSI EN 501 895
- EN 62511
- AS/NZS 2772.2
- AS/NZS 4268
- VCCI V-2, V-4, V-5
- KN-52

### EMC/RF Regulations and Standards (continued)

- KN-24
- CNS 15458

### Environmental Operating Temp

- 0°C to +40°C
- Non-Condensing Humidity

### Environmental Regulations

- RoHS Directive 2011/65/EU
- WEEE Directive 2012/19/EU
- China RoHS

### Certified Operating Systems

- Windows 10 64-bit (Pro & Home)
- Windows 10 IoT
- Linux (Fedora)