

## NUC11TNFi3- Quad-Core i3 Fanless

### Stay Cool, Clean and Silent

The NUC11TNFi3, built with 11th Gen Intel® Core™ i3 Intel® UHD Graphics, and fanless “Porcoolpine” chassis, delivers the performance and innovation for small space and embedded solutions without the use of a blower or fan. Whether you’re creating a digital kiosk, deploying intelligent vending, or refreshing enterprise PCs, the NUC11TNFi3 can get the job done easily. With the option of Intel® Wi-Fi 6 and Bluetooth 5.1 and the option to run Windows® 10, Linux, or another OS, the NUC11TNFi3 delivers the flexibility to build the exact solution your situation needs.

### I/O Performance and Flexibility

The NUC11TNFi3 has some new features including, for the first time on a commercial NUC, a Thunderbolt™ 4 port. Combine that with two full-sized HDMI 2.0b ports to power up to quad brilliant 4K displays at 60 Hz. Suddenly your digital kiosks and intelligent vending machines have images that really pop and draw people in. This unit also features display emulation which enables various options including headless

operation, a second virtual display, and persistent displays. Equipped with dual USB 2.0 on the internal header, Porcoolpine allows for additional expansion IO if more USBs, Ethernet or Serial ports are needed. We can configure to your specific needs. And Porcoolpine is tested for 24/7 operation ensuring solutions that are built to last.

### Safe and Secure

With Intel® technology you can get ahead of security threats. The built-in hardware-enhanced security means you can keep data and credentials secure, perfect for installations such as digital kiosks and intelligent vending. In addition you can physically lock down your NUC11TNFi3 via the built-in Kensington lock or an optional locking VESA mount kit available from Simply NUC.

### Highlighted features

- 11th Gen Intel® Core™ i3-1115G4
- Intel® UHD Graphics
- Two DDR4-3200 SO-DIMM Sockets
- M.2 Slot Supports PCIe Gen 4 SSDs
- 2.5" SATA drive bay
- Dual HDMI 2.0b supporting 4K @ 60Hz
- Intel® 2.5 Gigabit LAN
- One Thunderbolt 4 Port
- One Thunderbolt 3 Port
- Three USB 3.2 Gen 2 Ports
- One USB 2.0 Port
- Digital Audio 7.1 Surround Sound
- TPM 2.0
- Legacy Serial on a DE-9M connector
- RP-SMA Dual-Band Antennas
- Front Panel Power Button
- 19V DC Jack (12-20v operation)
- Kensington Lock Support
- VESA Mount Kit
- 0-40C Operating Temperature

### Customization

- Supports DDR4 RAM 4GB-64GB
- Supports M.2 SSD 128GB-8TB
- Secondary M.2 Supports 2.5" SSD 128GB-8TB
- Intel® Wi-Fi 6 + Bluetooth 5.1
- Optional Back IO Panel
- Two USB 2.0 Internal Headers
- One RS-232 Serial Internal Header



### Simply NUC Services

You can order this NUC in your various configurations, as well as your corporate OS Image loaded and ready to deploy.

## Technical Specifications

### Processor

- Intel® Core™ i3-1115G4 Processor (1.9GHz@15W, up to 4.1GHz Turbo, 2 Cores, 4 Threads, 6MB L3 Cache)

### Storage Capabilities

- One M.2 Socket Supporting 22x80 M.2 SSDs, PCIe Gen 4
- One SATA 3 port for connection to 2.5" HDD or SSD

### Audio

- Up to 7.1 surround audio via HDMI

### Hardware Management Features

- Trusted Platform Module (TPM) 2.0
- AMT supported Ethernet Controller
- Voltage and temperature sensing
- ACPI-compliant power management control

### Graphics

- Intel® UHD Graphics
- Two HDMI 2.0b Ports with HDCP 2.2
- Built-in CEC for Both Ports
- Support for a 3rd and 4th monitor via Thunderbolt 4 with DisplayPort

### Peripheral Connectivity

- Intel® 2.5 Gigabit LAN
- Three Super-Speed USB 3.2 Gen 2 Ports (Two Front and One Rear)
- One Rear USB 2.0 Port
- Two Rear USB 3.2 Gen 2 Ports on Type-C Connector (One Thunderbolt 4; One Thunderbolt 3)
- Intel® Wi-Fi 6 + BT 5.1 AX201 module can be added as an upgrade option

### Baseboard Power Requirements

- 19V, 65W AC-DC power adapter with detachable power cord.

### Mechanical Chassis Information

- 7.5" x 4" x 3" (190mm x 102mm x 76mm)
- VESA Mount Kit (Plate and Screws)
- 1.5kg (3.4lbs) Fully-Assembled with Antennas (no 2.5in drive or power adapter)

### System Memory

- Two DDR4 SO-DIMM sockets, 64GB Max, 3200Mhz, 1.2V

### System Bios

- 64 Mb Flash EEPROM with Intel® Platform Innovation Framework for EFI Plug and Play
- Intel® Visual BIOS
- Intel® Express BIOS Update Support

### Front Panel Header

- Reset, HDD LED, Power LEDs, Power On/Off
- Vcc5/1A, 5Vsby2A, 3.3Vsby1A

### Expansion Capabilities

- One M.2 for Panel Expansion – incl. Dual LAN/USB 2.0 Expansion Panel
- Two USB 2.0 Ports on Two 1x4 Internal Headers
- Two Consumer Electronics Control Headers
- 2.5in Drive Mount for SATA drive

## Certification and Regulations

### Product Safety Regulations and Standards

- IEC 60950-1
- UL 60950-1
- EN 60950-1
- CAN/CSA-C22.2 No. 60950-1

### Environment Operating Temp

- 0° C to +40° C
- Non-condensing Humidity

### Storage Temperature

- -20° C to +70° C

### EMC/RF Regulations and Standards (Class B)

- FCC CFR Title 47, Chapter I, Part 15, Subparts B, C, E
- CISPR 52
- ICES-005
- EN 55052
- EN 55024
- ETSI EN 500 528
- ETSI EN 501 489-1

### Environmental Regulations

- RoHS Directive 2011/65/EU
- WEEE Directive 2012/19/EU
- China RoHS

### Certified Operating Systems

- Windows 10 64-bit (Pro & Home)
- Windows 10 IoT
- Windows Server 2019
- Linux (Fedora)